ForestWave

Lady Clarissa Lady Carina

Main particulars		Hold particulars		
Flag	Dutch	Grain capacity	264,000 cbft	
Port of registry	Delfzijl	Holds / hatches	2/2; box shaped, open hatch	
Built	2000, 2001	Hold 1 (lxwxh)	32,30 x 13,20 x 9,20 m	
Туре	MPP, dry cargo ship	Hold 2 (lxwxh)	32,30 x 13,20 x 9,20 m	
Class	Lloyds register	Deck capacity	32,20 x 13,54 + 32,20 x 13,54 m	
Ice class	1A Finnish-Swedish Ice Class	Hatch covers	Pontoon	
IMO nr.	9201803 (Lady Clarissa)	Moveable bulkheads	1	
	9201827 (Lady Carina)	Hold ventilation	6 air changes per hour b.e.h.	
General dimensions		Strenghts	Strenghts	
GT/NT	4.235 / 2.100	Tanktop	15 mts / sqm	
DWT summer sw	5.438 mts	Hatch cover	2 mts / sqm	
Draft fully laden sw	5,89 m			
LOA	108,50 m	Machinery		
LPP	102,95 m	Main engine	MAK 6M32 - 2880 kW	
Beam moulded	15,88 m	Bow thruster	300 kW	
Depth moulded	7,70 m	Speed / consumption	12 kn on 12 mts RMG 380	
Ballast airdraft	29,00 m	Port consumption	1,5 mts MGO dens max 0,86	
Distance WL/HC	6,58 m (in full ballast)			
			Speed and consumption figures are calculated basis sailing even keel, on max. bft 3, ds 3 and	
Container data		seawater temperature max.	0	
Intake	283 teu		Fuel supplied to be of latest ISO 8217 specs. For trading in any SECA the fuel oil to meet the requirements as per MARPOL Annex VI, regulation 14 and 18.3.	

Intake is always subject vessel's stability, trim, permissible weight, no restriction in line of sight.

Tank capacities	
MGO	
Fresh water	

Ballast water

305 cbm 25 cbm 2.560 cbm Vessel is equipped with an EGCS.

Bunkers shall not be commingled to avoid compatibility problems. Owners are participating in fuel quality testing services, new supplied fuel shall only be used when analysis is known.

ForestWave

Lady Clarissa Lady Carina



